

# W14 LOADER

## TABLE OF CONTENTS


SERIES/SECTION	SECTION NO.	FORM NO.
<b>10 SERIES-GENERAL</b>		
General Engine Specifications .....	1010	9-75616
Detailed Engine Specifications .....	1023	9-78646
Maintenance and Lubrication .....	1050	9-72536
Torque Chart .....	1051	9-72536
<b>20 SERIES-ENGINE</b>		
Engine Diagnosis .....	2001	9-76365
Engine Tune-Up .....	2002	9-76379
Cylinder Head, Valve Train and Camshaft .....	2015	9-76166
Cylinder Block, Sleeves, Pistons and Rods .....	2025	9-76176
Crankshaft, Main Bearings, Flywheel and Oil Seal Replacement .....	2035	9-76187
Lubrication System .....	2047	9-78667
Stall Checks and Engine Removal and Installation .....	2050	9-72536
Backhoe Throttle Cable Adjustment .....	2050A	9-72536
Air Cleaner and Spark Arrester .....	2051	9-72536
Cooling System .....	2055	9-76337
Reconditioning Case Engine Blocks .....	2290	8-21170
<b>30 SERIES-FUEL SYSTEM</b>		
Fuel System and Filters .....	3010	9-75207
Robert Bosch Fuel Injection Pump .....	3012	9-74937
Roosa Master Fuel Injectors .....	3013	9-74959
Electric Fuel Pump .....	3051	9-72536
Fuel Lines and Fuel Tank .....	3052	9-72536
<b>40 SERIES - HYDRAULICS</b>		
Hydraulic Diagram, Trouble Shooting, Testing and Adjustments .....	4011	9-72536
Backhoe Hydraulic Diagrams, Trouble Shooting, Pressure Checks .....	4011A	9-72536
Hydraulic Pump .....	4012	9-72536
L51290 and L52776 Loader Control Valves .....	4020	9-72536
Case Backhoe Control Valve .....	4022	9-72536
L55038 Diverter Valve .....	4027	9-72536
L56060 Backhoe Relief Valve .....	4042	9-72536
Loader Cylinders .....	4050	9-72536
Backhoe Cylinders .....	4051	9-72536
<b>50 SERIES-STEERING</b>		
Hydraulic Diagram, Trouble Shooting and Testing .....	5011	9-72536
Steering Control Valve and Flow Control Valve .....	5013	9-72536
Steering Cylinders .....	5015	9-72536
Center Pivot .....	5018	9-72536



SERIES/SECTION	SECTION NO.	FORM NO.
<b>60 SERIES-POWER TRAIN</b>		
Allison Transmissions - Powershift Model . . . . .	Manual	SA 1277
Transmission Removal and Installation . . . . .	6012	9-72536
Differentials and Planetaries . . . . .	6020	9-72536
Rear Axle Trunnion Center Bearing Support, Drive Shafts and Universal Joints . . . . .	6022	9-72536
<b>70 SERIES-BRAKES</b>		
Air System Operation and Diagram . . . . .	7011	9-72536
Pressurizing/Depressurizing the Air System . . . . .	7012	9-72536
Brake Shoes and Wheel Cylinders . . . . .	7013	9-72535
L52092 Air Compressor, Governor and Reservoir . . . . .	7014	9-72536
L17683 Air Compressor . . . . .	7014A	9-72535
Brake Valve . . . . .	7015	9-72536
Brake Actuator . . . . .	7016	9-72535
Parking Brake Actuator and Control Valve . . . . .	7017	9-72536
Pressure Protection Valve and Pressure Reducing Valve . . . . .	7018	9-72536
Air Horn and Horn Valve . . . . .	7019	9-72535
Alcohol Evaporator . . . . .	7020	9-72535
Double Check Valve/Stop Light Switch . . . . .	7021	9-72536
<b>80 SERIES-ELECTRICAL</b>		
Wiring Diagram - Machines without Instrument Clusters . .	8011	9-72537
Trouble Shooting and Adjustments . . . . .	8012	9-72536
Batteries . . . . .	8014	9-72535
Starter, Starter Solenoid and Magnetic Switches . . . . .	8015	9-72536
35 amp Alternator, (Models without Instrument Cluster) . .	8016	9-72536
30 amp Alternator, (Models with Instrument Cluster) . . . .	8016A	9-72535
<b>90 SERIES-MOUNTED EQUIPMENT</b>		
Loader . . . . .	9011	9-72535
Model 26C Backhoe . . . . .	9012	9-72535
Roll-Over Protection Structure . . . . .	9019	9-72535

# Section 1010 GENERAL ENGINE SPECIFICATIONS W14 LOADER

THE MODEL AND ENGINE SERIAL NUMBER IS STAMPED ON A PLATE LOCATED ON THE SIDE OF THE ENGINE ABOVE THE CRANKING MOTOR.



## DIESEL ENGINES

### General

Type .....	4 Cylinder, 4 Stroke Cycle, Valve-in-Head
Firing Order .....	1-3-4-2
Bore .....	4-5/8 Inches
Stroke .....	5 Inches
Piston Displacement .....	336 Cubic Inches
Compression Ratio .....	16.5 to 1
No Load Governed Speed .....	2330 to 2370 RPM
Rated Engine Speed .....	2200 RPM
Engine Idling Speed .....	725 to 775 RPM
Exhaust Valve Rotators .....	Positive Type
*Valve Tappet Clearance (Exhaust) .....	(Hot) .020 Inch (Cold) .025 Inch
(Intake) .....	(Hot and Cold) .015 Inch

\*Hot Settings Are Made After the Engine Has Operated At Thermostat Controlled Temperature For At Least Fifteen Minutes.

Cranking Motor .....	24 Volt Negative Ground
Thermostat Operating Range .....	175°F. to 202°F.

### Piston and Connecting Rods

Rings per Piston .....	3
Number of Compression Rings .....	2
Number of Oil Rings .....	1
Type Pins .....	Full Floating Type
Type Bearing .....	Replaceable Precision, Steel Back, Copper-Lead Alloy Liners

### Main Bearings

Number of Bearings .....	5
Type Bearings .....	Replaceable Precision Steel Back, Copper-Lead Alloy Liners

### Engine Lubricating System

Oil Pressure .....	45 to 60 Pounds with Engine Warm and Operating at Rated Engine Speed
Type System .....	Pressure and Spray Circulation
Oil Pump .....	Gear Type
Oil Filter .....	Full Flow Spin on Type
Engine Oil Capacity (without filter change) .....	10 U.S. Quarts
(with filter change) .....	11 U.S. Quarts

### Fuel System

Fuel Injection Pump .....	Robert Bosch, Type PES Multiple Plunger
Pump Timing .....	31 Degrees Before Top Dead Center (Port Closing)
Fuel Injectors .....	Pencil Type (Opening Pressure 3200 PSI)
Fuel Transfer Pump .....	Plunger Type, Integral Part of Injection Pump
Governor .....	Variable Speed, Fly-Weight Centrifugal Type, Integral Part of Injection Pump
1st Stage Fuel Filter .....	Full Flow Spin on Type
2nd Stage Fuel Filter .....	Full Flow Spin on Type



## TABLE OF CONTENTS

RUN-IN INSTRUCTIONS .....	4
<b>ENGINE SPECIFICATION DETAILS</b>	
Cylinder Sleeves .....	5
Piston with 1.62" (41.15 mm) Pin Bore .....	5
Piston with 1.80" (45.72 mm) Pin Bore .....	5
Piston Pin for Piston with 1.62" (41.15 mm) Pin Bore .....	5
Piston Pin for Piston with 1.80" (45.72 mm) Pin Bore .....	5
Piston Rings .....	6
Connecting Rod for Piston with 1.62" (41.15 mm) Pin Bore .....	6
Connecting Rod for Piston with 1.80" (45.72 mm) Pin Bore .....	6
Crankshaft with 3" (76.2 mm) Main Bearing Journals .....	7
Crankshaft with 3.5" (88.9 mm) Main Bearing Journals .....	7,8
Camshaft .....	8
Valve Push Rod Lifters .....	8
Gear Train .....	9
Oil Pump and Two Gear Balancer .....	9
Oil Pump and Three Gear Balancer .....	9
Oil Pump, Front Mounted .....	10
Cylinder Head .....	10
Exhaust Valve .....	10
Intake Valve .....	10
Intake and Exhaust Valve Guides .....	11
Valve Spring .....	11
Rocker Arm Assembly .....	11
Intake Valve Timing .....	11
SPECIAL TORQUES .....	12,13
GENERAL TORQUES SPECIFICATION TABLE .....	14

## RUN-IN INSTRUCTIONS

### Engine Lubrication

Fill the engine crankcase with CASE HDM oil and install new engine oil filters, after an engine has been rebuilt.

**NOTE:** Use a *SERIES 3 DS or CD SERVICE CLASSIFICATION* oil that has the correct viscosity rating for ambient air temperature, if CASE HDM oil is not used.

Change the engine oil while the engine is hot and replace the engine oil filters, after the first 20 hours of operation.

Change the engine oil and filters at the given intervals, after the 20 hours, as found in the Operator's Manual.

### Run-In Procedure For Rebuilt Engines (With A Dynamometer)

The following procedure must be followed when using a PTO dynamometer to run-in the engine. The dynamometer will make sure of the control of the engine load at each speed and will remove stress on new parts during run-in.

During the run-in, continue to check the oil pressure, coolant level and coolant temperature.

STEP	TIME	ENGINE SPEED	DYNAMOMETER SCALE LOAD*
1	**10 Minutes	1000 RPM	Not Any
2	**10 Minutes	1800 RPM	Not Any
3	20 Minutes	1800 RPM	1/3
4	20 Minutes	1800 RPM	1/2
5	***30 Minutes	100 RPM below rated speed	3/4
6	Tighten the cylinder head bolts to the torque that is found in Section 2015 of the service manual.		

\* According to normal dynamometer scale load at rated speed for the specific vehicle model. Decrease this scale load as shown.

\*\* The best run-in procedure will constantly change the throttle between 750 to 1000 RPM, for the first 10 minutes and from 1000 to 1800 RPM, for the next 10 minutes. The purpose of this changing RPM is to change the lubrication and coolant flow.

\*\*\* 30 minutes at 3/4 load is a minimum amount of time the engine can be run. It is best that when possible, the engine (especially a turbocharged diesel) must be run for four (4) hours or more, at the above speed and load before checking the full engine horsepower or before using the engine for heavy field work.

### Run-In Procedure For Rebuilt Engines (Without A Dynamometer)

STEP	TIME	ENGINE SPEED	LOAD
1	*10 Minutes	1000 RPM	Not Any
2	*10 Minutes	1800 RPM	Not Any
3	30 Minutes	2/3 Rated RPM	Light Load
4	1 Hour	Full RPM (not over 2000 RPM)	80 to 90%
5	Tighten the cylinder head bolts to the torque that is found in Section 2015 of the service manual.		

\* If engine must then run at or near full load to operate the machine, remove the load for the first hour and run at high idle for several minutes at 15 minute intervals.

### Run-In Procedure

Keep in one gear lower than normal for the first 8 hours of field operation. DO NOT "lug" the engine for the next 12 hours. Prevent "lugging" by moving the shift lever to a lower gear. The engine must not be "lugged" below the Rated Engine RPM during the early hours of life.

## DETAILED ENGINE SPECIFICATIONS

### Cylinder Sleeves

	U.S. Value	Metric Value
Type .....	Wet, Can Be Replaced	
Material .....	Cast Iron	
ID of Sleeve .....	4.6250 to 4.6263"	117.475 to 117.508 mm
Maximum Service Limit .....	4.6283"	117.559 mm
Sleeve Out of Round (Installed in Block) .....	0.002"	0.0508 mm
Maximum Service Limit .....	0.002"	0.0508 mm
Taper (Installed in Block) .....	0.001"	0.0254 mm
Maximum Service Limit .....	0.002"	0.0508 mm
Clearance at Bottom of Piston, 90 Degree to Piston Pin ..	0.0052 to 0.0075"	0.1321 to 0.1905 mm
Maximum Service Limit .....	0.010"	0.254 mm

### Piston with 1.62" (41.15 mm) Pin Bore

Type .....	Cam Ground	
Material .....	Aluminum Alloy	
OD at Bottom, 90 Degree to Piston Pin .....	4.6188 to 4.6198"	117.3175 to 117.3429 mm
Minimum Service Limit .....	4.6178"	117.2921 mm
ID of Piston Pin Bore .....	1.6251 to 1.6253"	41.2775 to 41.2826 mm
Maximum Service Limit .....	1.6258"	41.2953 mm
Width of 1st Ring Groove .....	0.097 to 0.098"	2.464 to 2.489 mm
Maximum Service Limit .....	0.0985"	2.502 mm
Width of 2nd Ring Groove .....	0.097 to 0.098"	2.464 to 2.489 mm
Maximum Service Limit .....	0.0985"	2.502 mm
Width of 3rd Ring Groove .....	0.188 to 0.189"	4.775 to 4.801 mm
Maximum Service Limit .....	0.190"	4.826 mm

### Piston with 1.80" (45.72 mm) Pin Bore

Type .....	Cam Ground	
Material .....	Aluminum Alloy	
OD at Bottom, 90 Degree to Piston Pin .....	4.6188 to 4.6198"	117.3175 to 117.3429 mm
Minimum Service Limit .....	4.6178"	117.2921 mm
ID of Piston Pin Bore .....	1.8001 to 1.8005"	45.7225 to 45.7327 mm
Maximum Service Limit .....	1.8010"	45.7454 mm
Width of 1st Ring Groove .....	Not Measurable	
Width of 2nd Ring Groove .....	Not Measurable	
Width of 3rd Ring Groove .....	0.188 to 0.189"	4.775 to 4.801 mm
Maximum Service Limit .....	0.190"	4.826 mm

### Piston Pin for Piston with 1.62" (41.15 mm) Pin Bore

Type .....	Floats	
OD of Pin .....	1.6244 to 1.6246"	41.2598 to 41.2648 mm

### Piston Pin for Piston with 1.80" (45.72 mm) Pin Bore

Type .....	Floats	
OD of Pin .....	1.7994 to 1.7996"	45.7048 to 45.7098 mm

**Piston Rings**

	U.S. Value	Metric Value
Number One Compression (Top) .....	Rectangular Type	
End Gap in 4.625" (117.475 mm) ID sleeve .....	0.015 to 0.025"	0.381 to 0.635 mm
Maximum Service Limit .....	0.030"	0.762 mm
Side Clearance .....	0.0035 to 0.005"	0.089 to 0.127 mm
Maximum Service Limit .....	0.006"	0.152 mm
Number One Compression (Top) .....	Keystone Type	
End Gap in 4.625" (117.475 mm) ID Sleeve .....	0.015 to 0.025"	0.381 to 0.635 mm
Maximum Service Limit .....	0.030"	0.762 mm
Side Clearance .....	Not Measureable	
Number Two Compression (Intermediate) .....	Rectangular Type	
End Gap in 4.625" (117.475 mm) ID Sleeve .....	0.013 to 0.023"	0.330 to 0.584 mm
Maximum Service Limit .....	0.028"	0.711 mm
Side Clearance .....	0.003 to 0.005"	0.076 to 0.127 mm
Maximum Service Limit .....	0.006"	0.152 mm
Number Two Compression (Intermediate) .....	Keystone Type	
End Gap in 4.625" (117.475 mm) ID Sleeve .....	0.015 to 0.025"	0.381 to 0.635 mm
Maximum Service Limit .....	0.030"	0.762 mm
Side Clearance .....	Not Measureable	
Number Three Oil Control Ring (Bottom) .....	Two Piece	
Width .....	0.1860 to 0.1865"	4.7244 to 4.7371 mm
End Gap in 4.625" (117.475 mm) ID Sleeve .....	0.016 to 0.026"	0.406 to 0.660 mm
Maximum Service Limit .....	0.031"	0.787 mm
Side Clearance .....	0.0015 to 0.003"	0.038 to 0.076 mm
Maximum Service Limit .....	0.0035"	0.089 mm

**Connecting Rod for Piston with 1.62" (41.15 mm) Pin Bore**

Bushing .....	Replaceable	
Bushing ID, Installed (Ream to Size) .....	1.6254 to 1.6258"	41.2852 to 41.2953 mm
Maximum Service Limit .....	1.6265"	41.3131 mm
Bearing Liners .....	Replaceable	
Bearing Liner Width .....	1.586 to 1.596"	40.284 to 40.538 mm
Bore ID without Liners .....	2.9003 to 2.9013"	73.6676 to 73.6930 mm
Bearing Oil Clearance .....	0.0013 to 0.0038"	0.033 to 0.0965 mm
Maximum Service Limit .....	0.0043"	0.1092 mm
Undersize Bearings for Service .....	0.002, 0.010, 0.020, 0.030"	0.051, 0.254, 0.508, 0.762 mm
Side Clearance .....	0.007 to 0.016"	0.178 to 0.406 mm

**Connecting Rod for Piston with 1.80" (45.72 mm) Pin Bore**

Bushing .....	Replaceable	
Bushing ID, Installed (Ream to Size) .....	1.8004 to 1.8008"	45.7302 to 45.7403 mm
Maximum Service Limit .....	1.8015"	45.7581 mm
Bearing Liners .....	Replaceable	
Bearing Liner Width .....	1.586 to 1.596"	40.284 to 40.538 mm
Bore ID without Liners .....	3.1503 to 3.1513"	80.176 to 80.043 mm
Bearing Oil Clearance .....	0.0013 to 0.0038"	0.033 to 0.0965 mm
Maximum Service Limit .....	0.0043"	0.1092 mm
Undersize Bearings for Service .....	0.002, 0.010, 0.020, 0.030"	0.051, 0.254, 0.508, 0.762 mm
Side Clearance .....	0.007 to 0.016"	0.178 to 0.406 mm

**Crankshaft with 3" (76.2 mm) Main Bearing Journals**

	U.S. Value	Metric Value
Type .....	Forged, Heat Treated and Balanced	
End Play, Number Three Main Bearing Cap .....	0.003 to 0.015"	0.076 to 0.381 mm
Thrust Bearing, Standard Thickness .....	0.184 to 0.186"	4.674 to 4.724 mm
Thrust Bearing, Oversize Thickness for Service .....	0.190 to 0.192"	4.826 to 4.877 mm
Connecting Rod Journal Width .....	1.9975 to 2.0025"	50.7365 to 50.8635 mm
Connecting Rod Journal, Standard OD .....	2.748 to 2.749"	69.799 to 69.825 mm
0.010" (0.254 mm) OD Undersize, Grind to .....	2.738 to 2.739"	69.545 to 69.571 mm
0.020" (0.508 mm) OD Undersize, Grind to .....	2.728 to 2.729"	69.291 to 69.317 mm
0.030" (0.762 mm) OD Undersize, Grind to .....	2.718 to 2.719"	69.037 to 69.063 mm
Connecting Rod Journal Maximum Taper .....	0.0005"	0.0127"
Connecting Rod Journals Out of Round .....	0.0005"	0.0127 mm
Main Bearing Liners .....	Replaceable	
Main Bearing Liner Width, 1st, 3rd and 5th .....	2.1515 to 2.1615"	54.648 to 54.9021 mm
Main Bearing Liner Width, 2nd and 4th .....	1.151 to 1.161"	29.235 to 29.489 mm
Main Bearing Oil Clearance .....	0.0016 to 0.0046"	0.0406 to 0.1168 mm
Maximum Service Limit .....	0.005"	0.127 mm
Undersize Main Bearing Liners for Service .....	0.002, 0.010, 0.020, 0.030"	0.051, 0.254, 0.508, 0.762 mm
Main Bearing Journal, Standard OD .....	2.998 to 2.999"	76.149 to 76.175 mm
0.010" (0.254 mm) OD Undersize, Grind to .....	2.988 to 2.989"	75.895 to 75.921 mm
0.020" (0.508 mm) OD Undersize, Grind to .....	2.978 to 2.979"	75.641 to 75.667 mm
0.030" (0.762 mm) OD Undersize, Grind to .....	2.968 to 2.969"	75.387 to 75.413 mm
Main Bearing Journal Bore ID without Liners .....	3.191 to 3.192"	81.051 to 81.077 mm
Main Bearing Journal Width		
2nd and 4th .....	1.555 to 1.570"	39.497 to 39.878 mm
3rd .....	2.623 to 2.627"	66.624 to 66.726 mm
5th .....	2.6175 to 2.6325"	66.4845 to 66.8655 mm

**Crankshaft with 3.5" (88.9 mm) Main Bearing Journals**

Type .....	0.003 to 0.015"	0.076 to 0.381 mm
Thrust Bearing, Standard Thickness .....	0.155 to 0.157"	3.937 to 3.988 mm
Thrust Bearing, Oversize Thickness for Service .....	0.161 to 0.163"	4.089 to 4.140 mm
Connecting Rod Journal Width .....	1.9775 to 2.0025"	50.2285 to 50.8635 mm
Connecting Rod Journal, Standard OD .....	2.998 to 2.999"	76.149 to 76.175 mm
0.010" (0.254 mm) OD Undersize, Grind to .....	2.988 to 2.989"	75.895 to 75.921 mm
0.020" (0.508 mm) OD Undersize, Grind to .....	2.978 to 2.979"	75.641 to 75.667 mm
0.030" (0.762 mm) OD Undersize, Grind to .....	2.968 to 2.969"	75.387 to 75.413 mm
Connecting Rod Journal Maximum Taper .....	0.0005"	0.0127 mm
Connecting Rod Journal Out of Round .....	0.0005"	0.0127 mm
Main Bearing Liners .....	Replaceable	
Main Bearing Liner Width, 1st, 3rd and 5th .....	2.1515 to 2.1615"	54.6481 to 54.9021 mm
Main Bearing Liner Width, 2nd and 4th .....	1.214 to 1.224"	30.836 to 31.089 mm
Main Bearing Oil Clearance .....	0.0016 to 0.0046"	0.0406 to 0.1168 mm
Maximum Service Limit .....	0.005"	0.127 mm
Undersize Main Bearing Liners for Service .....	0.002, 0.010, 0.020, 0.030"	0.051, 0.254, 0.508, 0.762 mm



### Crankshaft with 3.5" (88.9 mm) Main Bearing Journals (Continued)

	U.S. Value	Metric Value
Main Bearing Journal, Standard OD .....	3.498 to 3.499"	88.849 to 88.875 mm
0.010" (0.254 mm) OD Undersize, Grind to .....	3.488 to 3.489"	88.595 to 88.621 mm
0.020" (0.508 mm) OD Undersize, Grind to .....	3.478 to 3.479"	88.341 to 88.367 mm
0.030" (0.762 mm) OD Undersize, Grind to .....	3.468 to 3.469"	88.087 to 88.113 mm
Main Bearing Journal Bore ID without Liners .....	3.691 to 3.692"	93.751 to 93.777 mm
<b>Main Bearing Journal Width</b>		
2nd and 4th .....	1.618 to 1.633"	41.097 to 41.478 mm
3rd .....	2.561 to 2.565"	65.049 to 65.151 mm
5th .....	2.5855 to 2.6005"	65.6717 to 66.0527 mm

### Camshaft

Type .....	Parabolic	
Bushings .....	Four, Replaceable	
Bushing Lubrication .....	Under Pressure	
ID of Bushings .....	2.2484 to 2.2514"	57.1094 to 57.1856 mm
Maximum Service Limit .....	2.2524"	57.2110 mm
<b>Bushing Width</b>		
1st (Front) .....	1.646 to 1.666"	41.808 to 42.316 mm
2nd and 3rd .....	1.4275 to 1.4475"	36.2585 to 36.7665 mm
4th .....	1.1462 to 1.1662"	29.1135 to 29.6215 mm
OD of Each Bearing Surface .....	2.2460 to 2.2470"	57.0484 to 57.0738 mm
Minimum Service Limit .....	2.2455"	57.0357 mm
Thrust Washer Thickness .....	0.1225 to 0.1275"	3.1115 to 3.2385 mm
Minimum Service Limit .....	0.1215"	3.0861 mm
<b>Thrust Plunger Spring:</b>		
Free Length .....	3.6250"	92.075 mm
OD of Spring .....	0.406"	10.312 mm
Compress to 2.750" (69.85 mm) .....	45 to 55 lbs.	200 to 245 N

### Valve Push Rod Lifters

OD of Lifter Stem, Standard .....	0.8097 to 0.8102"	20.566 to 20.579 mm
OD of Lifter Stem, Oversize for Service .....	0.8190 to 0.8195"	20.803 to 20.815 mm
ID of Block Bore, Standard .....	0.8118 to 0.8130"	20.620 to 20.650 mm
Maximum Service Limit .....	0.8135"	20.663 mm
ID of Block Bore, Oversize for Service .....	0.8215 to 0.8225"	20.866 to 20.891 mm

## Gear Train

	U.S. Value	Metric Value
Backlash		
Crankshaft Gear to Camshaft Gear .....	0.004 to 0.011"	0.1016 to 0.2794 mm
Idler Drive Gear to Idler Gear .....	0.003 to 0.010"	0.0762 to 0.2540 mm
Idler Gear to Fuel Pump Gear .....	0.004 to 0.012"	0.1016 to 0.3048 mm
Crankshaft Gear to Oil Pump Idler Gear .....	0.006 to 0.011"	0.1524 to 0.2794 mm
Crankshaft Gear to Fuel Pump Gear .....	0.027" max.	0.6858 mm max.
OD of Idler Gear Shaft .....	1.7325 to 1.7330"	44.0055 to 44.0182 mm
ID of Idler Gear Bushing .....	1.7345 to 1.7355"	44.0563 to 44.0817 mm
Maximum Service Limit .....	1.7375"	44.132 mm
Idler Gear Thrust Washer Thickness .....	0.061 to 0.063"	1.5494 to 1.6002 mm
Idler Gear Lateral Movement .....	0.002 to 0.012"	0.051 to 0.305 mm

## Oil Pump and Two Gear Balancer

Positive Displacement Pump .....	Gear Type	
Pump Gears to Cover Clearance .....	0.005" max.	0.127 mm max.
Backlash		
Crankshaft Gear to Counterweight Gear .....	0.008 to 0.013"	0.203 to 0.330 mm
Counterweight Gear to Counterweight Gear .....	0.005 to 0.013"	0.127 to 0.330 mm
Counterweight Shaft Bushing Wear .....	0.007" max.	0.178 mm max.
Relief Valve Spring		
Free Length .....	2.06"	52.324 mm
Wire Diameter .....	0.071"	1.803 mm
OD of Spring .....	0.680"	17.272 mm
Number of Coils .....	12	12
Compress to 1.252" (31.801 mm) .....	17.25 to 19.05 lbs.	77 to 85 N

## Oil Pump and Three Gear Balancer

Positive Displacement Pump .....	Gear Type	
Pump Gears to Cover Clearance .....	0.005" max.	0.127 mm max.
Backlash		
Crankshaft Gear to Counterweight Gear .....	0.008 to 0.13"	0.203 to 0.330 mm
Counterweight Gear to Counterweight Gear .....	0.005 to 0.013"	0.127 to 0.330 mm
Counterweight Gear and Drive Gear Bushing Wear .....	0.007" max.	0.178 mm max.
Relief Valve Spring		
Free Length .....	3.00"	76.2 mm
Wire Diameter .....	0.062"	1.575 mm
OD of Spring .....	0.515"	13.081 mm
Number of Coils .....	25	25
Compress to 1.68" (42.67 mm) .....	13.5 to 15.5 lbs.	60 to 69 N

**Oil Pump, Front Mounted**

	U.S. Value	Metric Value
Positive Displacement Pump	Gear Type	
Backlash		
Pump Gear to Crankshaft Gear	0.006 to 0.011"	0.1524 to 0.2794 mm
Pump Gears to Body Radial Clearance	0.0005 to 0.004"	0.013 to 0.102 mm
Pump Gears to Pump Cover Clearance	0.0015 to 0.005"	0.038 to 0.127 mm
Oil Pressure at High Idle, Hot Oil	40 to 65 PSI	276 to 448 kPa
Relief Valve Spring		
Number of Coils	11	11
Wire Diameter	0.080"	2.032 mm
Minimum ID	0.469"	11.913 mm
Free Length	2.00"	50.8 mm
Compress to 1.252" (31.801 mm)	23.8 to 25.6 lbs.	106 to 114 N
Relief Valve Cup Plug Depth	0.327"	8.306 mm

**Cylinder Head**

Warpage	0.005"	0.127 mm
---------	--------	----------

**Exhaust Valve**

Tappet Clearance	0.025"	0.635 mm
Face Angle	44 Degrees	44 Degrees
Face Run-Out	0.002" max.	0.051 mm max.
OD of Head	1.745 to 1.755"	44.323 to 44.577 mm
OD of Stem	0.402 to 0.403"	10.211 to 10.236 mm
Minimum Service Limit	0.4018"	10.206 mm
OD of Taper at 4.2675" (108.395 mm)	0.401 to 0.402"	10.185 to 10.211 mm
Minimum Service Limit	0.4008"	10.180 mm
Length	6.4195 to 6.4405"	163.055 to 163.589 mm
Insert Seat Angle	45 Degrees	45 Degrees
Seat Contact Width	0.0775 to 0.100"	1.9685 to 2.540 mm
Seat Run-Out	0.002"	0.051 mm
Insert Height	0.313 to 0.316"	7.950 to 8.026 mm
OD of Insert	1.9455 to 1.9465"	49.4157 to 49.4411 mm
ID of Insert	1.571 to 1.577"	39.903 to 40.056 mm

**Intake Valve**

Tappet Clearance	0.015"	0.381 mm
Face Angle	44 Degrees	44 Degrees
Face Run-Out	0.002" max.	0.051 mm
OD of Stem	0.402 to 0.403"	10.211 to 10.236 mm
Minimum Service Limit	0.4018"	10.206 mm
OD of Head	1.995 to 2.005"	50.673 to 50.927 mm
Length	6.4195 to 6.4405"	163.055 to 163.589 mm
Seat Angle	45 Degrees	45 Degrees
Seat Contact Width	0.0750 to 0.0975"	1.905 to 2.477 mm
Seat Run-Out	0.002" max.	0.051 mm
Insert Height (If Equipped)	0.2775 to 0.2825"	7.0485 to 7.1755 mm
OD of Insert (If Equipped)	2.099 to 2.100"	53.315 to 53.340 mm
ID of Insert (If Equipped)	1.805 to 1.815"	45.847 to 46.101 mm

**Intake and Exhaust Valve Guides**

	U.S. Value	Metric Value
Length .....	3.219"	81.763 mm
OD of Guide .....	0.7510 to 0.7515"	19.075 to 19.088 mm
ID of Guide (Installed and Reamed) .....	0.4045 to 0.4055"	10.274 to 10.300 mm
Maximum Service Limit .....	0.4065"	10.325 mm
Protrusion Above Cylinder Head .....	0.953"	24.206 mm

**Valve Spring**

Free Length .....	2.18"	55.372 mm
Number of Coils .....	7.25	7.25
Wire Diameter .....	0.192"	4.877 mm
Compress Spring to 1.484" (37.694 mm), Valve Open .....	153 to 167 lbs.	681 to 743 N
Compress Spring to 1.937" (49.200 mm), Valve Closed .....	50.5 to 60.5 lbs.	225 to 269 N

**Rocker Arm Assembly**

OD of Shaft .....	0.872 to 0.873"	22.149 to 22.174 mm
ID of Arm Bore .....	0.8745 to 0.8755"	22.212 to 22.238 mm
Shaft Assembly Lateral Movement (Both Ends) .....	0.010 to 0.030"	0.254 to 0.762 mm
Shaft Spring		
Number of Working Coils .....	4	4
Wire Diameter .....	0.080"	2.032 mm
Compress Spring to 1.562" (39.675 mm) .....	8.5 to 11.5 lbs.	38 to 51 N
Lubrication .....	Engine Oil, Camshaft Metering	
Shaft Oil Holes .....	Toward Valve Side of Engine	
	Shaft Can Not Be Turned	

**Intake Valve Timing**

Valve Timing ..... With the Number One Intake Valve to Rocker Arm Clearance Set at 0.015" (0.381 mm) and the Dial Indicator on the Number One Valve Retainer, 0.053" (1.346 mm) Movement of the Valve From the Seat (Clockwise Pulley Rotation) Will Give One Complete Revolution Plus 7 Degrees after TC Timing Indication on the Crank Pulley.

1023-12

**Special Torques**

	U.S. Value	Metric Value
Camshaft Nut - With Lock Washer .....	95 to 105 ft. lbs.	129 to 142 Nm (12.9 to 14.2 kgm)
- With Hardened Washer .....	195 to 205 ft. lbs.	264 to 278 Nm (26.4 to 27.8 kgm)
Connecting Rod Bolts (Add Lubrication to Threads and Under Bolt Heads with 30W Oil) .....	95 to 105 ft. lbs.	129 to 142 Nm (12.9 to 14.2 kgm)
Crankshaft Pulley Bolt .....	100 to 110 ft. lbs.	136 to 149 Nm (13.6 to 14.9 kgm)
Crankshaft Pulley Nut .....	125 to 135 ft. lbs.	169 to 183 Nm (16.9 to 18.3 kgm)
Crankshaft Main Bearing Bolts .....	145 to 155 ft. lbs.	197 to 210 Nm (19.7 to 21.0 kgm)
- With Hardened Washers .....	200 to 210 ft. lbs.	271 to 285 Nm (27.1 to 28.5 kgm)
Oil Cooler Outlet Cover Screws .....	35 to 42 ft. lbs.	48 to 51 Nm (4.8 to 5.1 kgm)
Cylinder Head Bolts .....	200 to 210 ft. lbs.	271 to 285 Nm (27.1 to 28.5 kgm)
Cylinder Head Cover Stud Nuts .....	8 to 10 ft. lbs.	11 to 14 Nm (1.1 to 1.4 kgm)
Flywheel to Crankshaft Bolts Without Hardened Washers .....	180 to 190 ft. lbs.	244 to 258 Nm (24.4 to 25.8 kgm)
With Hardened Washers .....	230 to 250 ft. lbs.	312 to 339 Nm (31.2 to 33.9 kgm)
Intake and Exhaust Manifold Studs .....	25 to 30 ft. lbs.	34 to 41 Nm (3.4 to 4.1 kgm)
Exhaust Manifold Hex Nuts .....	25 to 30 ft. lbs.	34 to 41 Nm (3.4 to 4.1 kgm)
Intake Manifold Hex Nuts - Standard .....	25 to 30 ft. lbs.	34 to 41 Nm (3.4 to 4.1 kgm)
- Heavy .....	35 to 42 ft. lbs.	48 to 57 Nm (4.8 to 5.7 kgm)
Oil Pan Capscrews .....	15 to 20 ft. lbs.	20 to 27 Nm (2.0 to 2.7 kgm)
Oil Pan Drain Plug .....	29 to 31 ft. lbs.	39 to 42 Nm (3.9 to 4.2 kgm)



**Special Torques (Continued)**

	U.S. Value	Metric Value
Oil Pump Inlet Connector .....	105 to 115 ft. lbs.	142 to 156 Nm (14.2 to 15.6 kgm)
Oil Pump Inlet Tube Nut .....	95 to 105 ft. lbs.	129 to 142 Nm (12.9 to 14.2 kgm)
Rocker Arm Adjusting Screw Locknut .....	20 to 25 ft. lbs.	27 to 34 Nm (2.7 to 3.4 kgm)
Rocker Arm Bracket Stud Nut or Bolt .....	40 to 45 ft. lbs.	54 to 61 Nm (5.4 to 6.1 kgm)
Water Pump and Fan Shaft Nut - Standard .....	60 to 70 ft. lbs.	81 to 95 Nm (8.1 to 9.5 kgm)
- Crownlock .....	45 to 50 ft. lbs.	61 to 68 Nm (6.1 to 6.8 kgm)
Balancer Mounting Bolts - Grade 5 .....	80 to 96 ft. lbs.	108 to 130 Nm (10.8 to 13.0 kgm)
- Grade 8 .....	110 to 132 ft. lbs.	149 to 179 Nm (14.9 to 17.9 kgm)
Balancer Counterweight Set Screws .....	70 to 80 ft. lbs.	95 to 108 Nm (9.5 to 10.8 kgm)

### GENERAL TORQUE SPECIFICATION TABLE (Revised 11-73)

USE THE FOLLOWING TORQUES WHEN SPECIAL TORQUES ARE NOT GIVEN

**NOTE:** These values apply to fasteners as received from supplier, dry, or when lubricated with normal engine oil. They do not apply if special graphited or moly-disulphide greases or other extreme pressure lubricants are used. This applies to both UNF and UNC threads.

SAE Grade No.		5				8 ★			
Bolt head identification marks as per grade NOTE: Manufacturing Marks Will Vary									
Bolt Size		Torque				Torque			
		Foot Pounds		Newton-Meters		Foot Pounds		Newton-Meters	
Inches	Millimeters	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
1/4	6.35	9	11	12.2	14.9	12	15	16.3	20.3
5/16	7.94	17	20.5	23.1	27.8	24	29	32.5	39.3
3/8	9.53	35	42	47.5	57.0	45	54	61.0	73.2
7/16	11.11	54	64	73.2	86.8	70	84	94.9	113.9
1/2	12.70	80	96	108.5	130.2	110	132	149.2	179.0
9/16	14.29	110	132	149.2	179.0	160	192	217.0	260.4
5/8	15.88	150	180	203.4	244.1	220	264	298.3	358.0
3/4	19.05	270	324	366.1	439.3	380	456	515.3	618.3
7/8	22.23	400	480	542.4	650.9	600	720	813.6	976.3
1	25.40	580	696	786.5	943.8	900	1080	1220.4	1464.5
1-1/8	25.58	800	880	1084.8	1193.3	1280	1440	1735.7	1952.6
1-1/4	31.75	1120	1240	1518.7	1681.4	1820	2000	2467.9	2712.0
1-3/8	34.93	1460	1680	1979.8	2278.1	2380	2720	3227.3	3688.3
1-1/2	38.10	1940	2200	2630.6	2983.2	3160	3560	4285.0	4827.4

★ Thick nuts must be used with Grade 8 bolts

# Section 1050

MAINTENANCE  
AND  
LUBRICATION



## MAINTENANCE CHART

**CAUTION:** The following chart is based on maximum intervals. If machine operates in severe conditions, service more often.

INTERVAL	SERVICE	INSTRUCTIONS
Run-In: Every Two Hours Until Stabilized	Torque wheel nuts 380-420 foot-pounds, dry threads. Torque axle mounting bolts 380-460 foot-pounds, dry threads.	
Run-In: After First 20 Hours	Change engine oil Change engine oil filter. Check drive belt tension. Torque bucket pin bolts 75 foot-pounds, dry threads.	Section 23 Section 7014 and 8016
Every 10 Hours Or Daily	Grease frame pivot points. Grease loader pivot points. Grease rear axle trunnion pivot points. Check engine oil level. Check radiator coolant level. Drain air reservoir. Visually inspect transfer pump sediment bowl for water. If found, drain water from bowl, fuel filters and fuel tank. Check machine and ground under machine for signs of leaks.	Section 31
Every 50 Hours Or Weekly, Whichever Comes First	Check master brake cylinder. Check transmission oil level. Drain Sediment bowl. Check hydraulic reservoir oil level. Grease front shaft support bearing. Grease steering cylinder pivots. Grease drive shaft universals & slip spline. Check battery fluid level.	Section 6012 Section 4011 Section 8014

INTERVAL	SERVICE	INSTRUCTIONS
Every 100 Hours	Clean spark arresting muffler.	
Every 150 Hours	Change engine oil.	
Every 250 Hours	Grease equipment control levers. Check front and rear axle oil levels. Clean alcohol evaporator intake filter.	Section 6020 Section 7020
Every 300 Hours	Change engine oil filter.	Section 23
Every 500 Hours	Change first and second stage fuel filters and fuel transfer pump filter. Check drive belt tension. Drain water from fuel tank. Clean electric fuel pump filter.	Section 31 Section 7014 and 8016
Every 1000 Hours Or Yearly, Whichever Comes First	Change hydraulic oil. Change hydraulic reservoir outlet filter. Change transmission oil. Change transmission filter. Clean transmission suction strainer. Clean transmission breather. Change front and rear axle oil. Clean air compressor cylinder head (by dealer only)	Section 4011 Section 4011 Section 6012 Section 6012 Section 6012 Section 6012 Section 6020 Section 7014
Every 2000 Hours Or Yearly, Whichever Comes First	Clean and refill cooling system. Disassemble and clean alcohol evaporator and replace all gaskets (by dealer only).	Section 7020
Every 3000 Hours	Rebuild/replace air compressor (by dealer only).	Section 7014
As Required	Service air cleaner when restriction indicator shows red signal band.  After wheel has been removed for servicing and reinstalled, check wheel nut torque every two hours until stabilized. Torque 380-420 foot-pounds.  Each time bucket is removed and reinstalled, torque bucket pin bolts 75 foot-pounds, dry threads. After 20 hours, check torque and if necessary retorque to 75 foot-pounds.	Section 2051

## FLUIDS AND LUBRICANTS

COMPONENT	CAPACITY		SPECIFICATIONS
	U. S.	Metric	
Fuel tank	38 gals.	144 liters	No. 2 diesel fuel
Cooling system	28 qts.	27 liters	1/2 high boiling point, permanent antifreeze; 1/2 water (protects down to -34° F.)
Engine crankcase: Without filter change With filter change	10 qts. 11 qts.	9,4 liters 10,4 liters	Engine oil: Case HDM Oil CD - Commercial class D (Series 3, MIL-L-45199) Above 32° F. - SAE 30 10° to 50° F. - SAE 20W Below 32° F. - SAE 10W
Brake master cylinders			SAE J1703c brake fluid
Equipment and steering hydraulic system: System total Reservoir refill	21 gals. 16 gals.	80 liters 61 liters	Case TCH Fluid. Alternate oils: Tenneco Hytrans Fluid. Engine oil - SD - Service class D or CA - Commercial class A. Above 32° F. - SAE 10W. Below 32° F. - SAE 5W.
Axles: Each center bowl Each wheel end	9-1/2 qts. 3 pts.	9 liters 1,4 liters	Case FDL -15° F. (-26° C) and above Alternate oils: Hypoid Gear Oil, API-GL-5 SAE 90 or SAE 80W/90 -15° F. (-26° C) and above SAE 80W - -15° F. (-26° C) to +70° F. (+21° C) SAE 75W - -40° F. (-4° C) to +35° F. (+2° C)
Pressure fittings			No. 2 moly-disulfide grease Alternate: Multipurpose lithium- soap base grease.
Alcohol evaporator	1 pt.	0,5 liters	Clean wood alcohol.
Transmission-converter: System total Transmission refill	9 gals. 7-1/2 gals.	34 liters 28 liters	Case TCH Fluid. Alternate oils: Type C-2 transmission hydraulic fluid such as Tenneco Hytrans Fluid.

# Section 2001

## ENGINE DIAGNOSIS

