

Electronic Diesel Control Repair Manual



EDC M(S) 5 - D 2842 LE 6..



Dear Customer

These instructions are intended to help you properly carry out repairs on the electronically controlled diesel injection system described in this document.

In writing these instructions, we have assumed that you have the necessary knowledge of control systems for working on and with the electronic diesel control.

Best regards
MAN Nutzfahrzeuge Aktiengesellschaft
Nuremberg Plant

Since our products are in continuous development, we reserve the right to make technical modifications.

© 2002 MAN Nutzfahrzeuge Aktiengesellschaft
Reprint, duplication or translation, as a whole or in part without the written approval of MAN is prohibited.
MAN reserves all rights accorded by the relevant laws on copyright.



Contents

Safety information	4
Electronic diesel control	6
System description	7
Component description	9
Control unit plug connector	9
Injection pump	11
Electromagnetic fuel-delivery regulator	11
Resistor bank	12
Electrohydraulic shut-off device EHAB	13
Drive stage selection	16
Turbo air and coolant temperature sensors	17
Turbo pressure sensor (51.27421–0181)	18
RPM sensor	19
Notes on operation	20
Self-diagnosis	21
Flash code	22
List of checking procedures	24
Troubleshooting chart	27
Troubleshooting program	30
Test	31
Drive stage selection	31
RPM sensor	32
Boost pressure sensor	33
Control rod position sensor	34
Coolant temperature sensor	35
Resistor bank	36
Fuel volume regulator	37
Auxiliary rpm sensor	38
Charge-air temperature sensor	39
Undervoltage	40
Control unit	41
Engine overspeed	42
EDC control box for idle speed adjustment	43
CAN system (control unit)	44
Main relay	45
Atmospheric pressure sensor (in control unit)	46
CAN system (TSC1-FM message)	47
Control unit, EEPROM processor 1 fault	48
Control unit, EEPROM processor 2 fault	49
Control unit (processor run-on)	50
Control unit watchdog run-on fault	51
Control rod position sensor – loose contact	52
PBM interface	53
Electrohydraulic shut-off device EHAB	54

Plug connections	55
Rating data sheet	57
Revision list	57
Scope	57
General features	57
Temperature range	58
Mechanical characteristics	59
Electrical ratings	60
Immunity to interference	61
Resistance to motor vehicle-specific liquids / fluids	62
Mechanical test data	62
Service life test	62
Connection diagram	63
Index	66

General

Important safety regulations are summarized in this quick-reference overview and arranged by topic to effectively convey the knowledge necessary to avoid accidents causing injury, damage or environmental hazard.

The engine operating manual contains further information.


Important:

Should an accident occur despite all precautionary measures, particularly one involving contact with corrosive acid, penetration of fuel under the skin, scalding by hot oil, antifreeze splashing into the eyes etc. **you must seek medical assistance immediately.**

1. Instructions for avoiding accidents likely to cause injury

Only authorized and qualified personnel are permitted to carry out inspection, adjustment and repair work

- Secure and chock vehicles to prevent the vehicle rolling
- Firmly secure units and assemblies on disassembly
- Only authorized personnel are permitted to start and operate the engine
- Do not stand too close to rotating parts while the engine is running
Wear close-fitting working clothes
- Do not touch a hot engine with bare hands:
Risk of burns
- Keep area surrounding engine, ladders and stairways free of oil and grease.
Accidents caused by slipping can have serious consequences
- Only work with tools which are in good condition. Damaged or worn spanners and wrenches can slip off: Risk of injury
- Persons must not stand under an engine suspended on a crane hook. Keep lifting gear in perfect condition
- Only open coolant circuit once the engine has cooled down. Follow the instructions given under "Care and Maintenance" in the Operating Manual exactly if it is not possible to avoid opening the coolant circuit with the engine at operating temperature





- Do not tighten or loosen pipes and hoses that are under pressure (lubricant circuit, coolant circuit and any downstream hydraulic oil circuits): Risk of injury caused by liquids escaping under pressure
- Do not place hands under the fuel jet when checking injection nozzles.
Do not inhale fuel mist
- Always disconnect battery when working on the electrical system
- Do not use rapid charger to start the engine. Rapid charging of batteries is only permitted with the positive and negative leads disconnected!
- Disconnect batteries only with the ignition turned off
- Observe manufacturer's instructions for handling batteries.
Caution:
Battery acid is toxic and corrosive. Battery gasses are explosive



- Only use suitable measuring instruments to **measure voltages!** The minimum input resistance of a measuring instrument should be 10 MΩ
- Only disconnect or connect wiring harness connectors on electronic control units with the **ignition turned off!**

Disconnect batteries and connect the positive lead to the negative lead such that they are electrically conductive before carrying out any electric welding work. Earth the welding set as close to the weld as possible. Do not place cables of welding set parallel to electrical lines in the vehicle.

Refer to the "Welders Code of Practice" for further accident prevention measures.

- **When carrying out repaint jobs**, electronic components may be subject to high temperatures (max. 95°C) for only very short periods; a period of up to approx. 2 hours is permissible at a max. temperature of 85°C, disconnect batteries

Limitation of liability for parts and accessories

In your own interest, we strongly recommend you use only accessories and original MAN parts expressly approved by MAN for your MAN engine. The reliability, safety and suitability of these parts and accessories have been tested specially for MAN engines. Despite us keeping a constant eye on the market, we cannot assess and be held responsible for these properties in other products, even if they bear TÜV (German testing and inspection institute) approval or any other official approval in any particular case.

Laying up or storage

Special measures must be implemented in accordance with MAN Company Standard M 3069 Part 3 if engines are to be laid up or placed into storage for more than 3 months.